VACUUBRAND®

高真空控制套装 （不锈钢） VACUU·SELECT + VACUU·VIEW extended, KF DN 25



网站链接

产品说明

VACUU·SELECT高真空控制套装能够用于真空度从常压到10^{-3}mbar区间的真空控制。套装包含：VACUU·SELECT真空控制器，高真空规，耐化学腐蚀的直通电磁阀VV-B 15C，以及通过小型法兰（KF）连接到真空系统所需的连接件。VACUUBRAND 提供带有两种不同小法兰连接的高真空控制套装。 KF DN 16 高真空控制套装与我们的旋片泵 RE / RZ 2.5 至 RE / RZ 6 以及我们的化学杂交泵 RC 6 兼容。 KF DN 25 高真空控制套装与我们的 VACUU·PURE 螺杆泵和 RE / RZ 9 旋片泵兼容。 凭借其直观的、基于应用程序的用户界面，用户能够利用控制器快速达到所需的高真空过程。对于复杂的工艺流程，可以修改预定义的应用程序，并创建新的应用程序来优化流程条件。搭配的直通电磁阀和真空规通过专用VACUU·BUS系统自动识别配置。

性能特点

- 此款高真空控制套装适用化学实验室所有高真空应用，真空控制范围为常压至高真空(10^{-3}mbar)
- 金属部件由不锈钢制成，具有更好的化学耐受性
- 图形化用户界面，操作简单
- 预定义的应用程序可提供快速、可重复的结果，应用程序编辑器可轻松定制
- 经久耐用的VACUU·VIEW extended真空规测量的真空度范围广泛，而且具有优异的耐化学腐蚀性和机械强度。

技术参数如有变化,恕不另行通知
© VACUUBRAND GMBH + CO KG | 2026

网站链接:
https://shop.vacuubrand.com/20700110

订购信息

产品名称	额定电源电压|工作频率	电源插头类型	订货号
VACUU·SELECT + VACUU·VIEW extended, KF DN 25	100-230 V | 50-60 Hz	CEE/CH/UK/US/AUS/CN	20700110

货品配置

高真空控制套装，包含：VACUU·SELECT真空控制器（未内置真空传感器及放气阀）配VACUU·VIEW extended传感器，电源，接口为KF DN 25的直通电磁阀和三通，异径小法兰KF DN 25/16,接口为DN 15mm的软管嘴接头（PP材质），卡箍和密封圈，连接后即可使用

配件

- VACUU·SELECT用户管理 VACUU·SELECT User Management (20700900)
- 橡胶真空管 DN 10 mm (20686002)
- 进气阀 VB M-B (20674217)
- VACUU·SELECT用户管理 VACUU·SELECT User Management (20700900)
- 橡胶真空管 DN 8 mm (20686001)
- 橡胶真空管 DN 8 mm (20686001)

技术参数如有变化,恕不另行通知
© VACUUBRAND GMBH + CO KG | 2026

网站链接:
https://shop.vacuubrand.com/20700110

技术指标

测量范围 (mbar)	1100 - 1 x 10^{-3} mbar
测量范围 (torr)	825 - 1 x 10^{-3} torr
控制范围 (mbar)	1000 - 1 x 10^{-3} mbar
控制范围 (torr)	750 - 1 x 10^{-3} torr
测量原理	陶瓷隔膜传感器+ 陶瓷夹套皮拉尼传感器
测量的不确定性	指示值的+- 15%，在0.01-5 mbar/hPa/torr的范围内 / +-3 mbar 为 > 5 mbar
真空传感器	VACUU·VIEW extended
温度系数	+- 0.2 mbar/hPa/0.15 torr /K
真空接头	KF DN 25 小法兰 / DN 15 mm 软管喷嘴接头
放气阀，接口	否
的允许环境温度范围（运行）	10 - 40 °C
的允许环境温度范围（存放）	-10 - 60 °C
最大介质温度（持续操作）	40 °C
短期内介质温度的最大值	80 °C
外壳材质	具有良好化学耐腐蚀性的坚固的塑料外壳
防护等级	IP 40
防护等级UL50E	Type 1
依据IEC 60529前面板的防护等级	IP 41
依据UL50E前面板的防护等级	Type 2
尺寸（长x宽x高）	152 x 127 x 41 mm
重量	0.6 kg
最大阻断容量/阻断电流， 24V/VACUU·BUS®	4 A
连接电缆长度	2 m
NRTL 标准	是

© VACUUBRAND GMBH + CO KG | 2026

通讯	Ethernet (RJ45): Modbus TCP / USB (Type A): Data transfer, software update, RS-232 (additional adapter required)

© VACUUBRAND GMBH + CO KG | 2026

VACUUBRAND®

尺寸规格表



© VACUUBRAND GMBH + CO KG | 2026

网站链接:
https://shop.vacuubrand.com/20700110

VACUUBRAND GMBH + CO KG
P.O. Box 1664
97877 Wertheim
T +49 9342 808 5550
F +49 9342 808 5555

info@vacuubrand.com
www.vacuubrand.com

VACUUBRAND

VACUUBRAND is part of the Brand group, a manufacturer of high-quality and innovative laboratory equipment and vacuum technology with a global team of approx. 1,000 employees.

With highly motivated and qualified employees, we manufacture the world's most comprehensive product family for vacuum generation, measurement and control for the rough and fine vacuum range in the laboratory.

All with one goal:
Enabling our customers to run reliable, safe and efficient processes. This is why we commit ourselves to continuous innovation, first-class performance, and outstanding quality.

Engineering excellence is central to our ability to deliver products and solutions renowned for their quality, durability, and reliability. Innovative technology, high quality materials and extensive testing deliver unmatched performance - engineered and manufactured in Germany.

Together with you, our experts will find the best solution for your application and provide you with first-class service along the way.

© VACUUBRAND GMBH + CO KG

BRAND (Shanghai) Trading Co., Ltd.
Shanghai, China

T +86 21 6422 2318
info@brand.com.cn
china.brand.com.cn

BRAND Scientific Equipment Pvt. Ltd.
Mumbai, India

T +91 22 42957790
customersupport@brand.co.in
www.brand.co.in

BRANDTECH® Scientific, Inc.
Essex, CT. United States of America

T +1 860 767 2562
info@brandtech.com
www.brandtech.com

BRANDGROUP®