

Vacuum gauge VACUU·VIEW extended

[Link to the website](#)



Product description

For the monitoring of your vacuum processes in the rough and fine vacuum range, the new vacuum gauges VACUU·VIEW extended are perfect! The heavy duty combination of ceramic diaphragm sensor and ceramic jacketed Pirani sensor ensures reliable readings in the wide range from atmosphere down to 10^{-3} mbar.

Performance features

- Precision and chemical resistance in an exceptionally wide range from atmosphere down to 10^{-3} mbar, one gauge only for both rough and fine vacuum
- compact design with integrated sensors for useful setup in laboratory and process
- the chemical resistant combination of ceramic diaphragm sensor and ceramic jacketed Pirani sensor ensures a long product life even with aggressive chemicals
- illuminated display, easy to read
- display with menu driven handling, easy to use e.g. for unit settings

Ordering data

Product name	Nominal mains voltage mains frequency	Plug type	Articleno.
VACUU-VIEW extended	100-230 V 50-60 Hz	CEE/CH/UK/US/AUS/CN	20683210

Items supplied

Vacuum gauge with integrated vacuum sensors, ready for operation, with kit hose nozzle DN 6/10 mm, wall-plug power supply and manual.


Accessories

- Rubber vacuum tubing DN 8 mm (20686001)

Technical data


Measuring range (mbar)	1100 - 1×10^{-3} mbar
Measuring range (torr)	825 - 1×10^{-3} torr
Measurement principle	Ceramic diaphragm sensor + ceramic jacketed Pirani sensor
Accuracy of measurement	+/- 15% of indicated value in the range 0.01-5 mbar / +/- 3 mbar for > 5 mbar
Vacuum sensor	Integr.
Temperature coefficient	+/- 0.2 mbar/hPa/0.15 torr /K
Vacuum sensor connection	Small flange KF DN 16 and hose nozzle DN 6/10 mm
Venting valve, connection	No
Permissible ambient temperature range (operation)	10 - 40 °C
Permissible ambient temperature range (storage)	-10 - 60 °C
Max. media temperature (continuous operation)	40 °C
Max. media temperature for short times	80 °C
Material of outer housing	Robust plastic housing with good chemical resistance
Protection class IEC 60529	IP 54
Protection class UL50E	Type 5
Protection class of front side according to IEC 60529	IP 54
Dimensions (L x W x H)	50 x 62 x 103 mm
Weight	0.19 kg
Cable length connection	2 m
ATEX conformity	II 3/- G Ex h IIC T4 Gc X Internal Atm. only
NRTL certification	Yes

Dimension sheet



Gewicht /
weight: 210 g

Innenvolumen /
Internal volume: 3.0 cm³



Alle Maße / all dimensions (mm)

Gewicht /
weight: 205 g

Innenvolumen /
Internal volume: 3.4 cm³

VACUUBRAND VACUU-VIEW
Version 2015/06/03

VACUUBRAND GMBH + CO KG
P.O. Box 1664
97877 Wertheim
T +49 9342 808 5550
F +49 9342 808 5555

info@vacuubrand.com
www.vacuubrand.com

VACUUBRAND®

VACUUBRAND is part of the Brand group, a manufacturer of high-quality and innovative laboratory equipment and vacuum technology with a global team of approx. 1,000 employees.

With highly motivated and qualified employees, we manufacture the world's most comprehensive product family for vacuum generation, measurement and control for the rough and fine vacuum range in the laboratory.

All with one goal:

Enabling our customers to run reliable, safe and efficient processes. This is why we commit ourselves to continuous innovation, first-class performance, and outstanding quality.

Engineering excellence is central to our ability to deliver products and solutions renowned for their quality, durability, and reliability. Innovative technology, high quality materials and extensive testing deliver unmatched performance - engineered and manufactured in Germany.

Together with you, our experts will find the best solution for your application and provide you with first-class service along the way.

BRAND (Shanghai) Trading Co., Ltd.
Shanghai, China

T +86 21 6422 2318
info@brand.com.cn
china.brand.com.cn

BRAND Scientific Equipment Pvt. Ltd.
Mumbai, India

T +91 22 42957790
customersupport@brand.co.in
www.brand.co.in

BRANDTECH® Scientific, Inc.
Essex, CT. United States of America

T +1 860 767 2562
info@brandtech.com
www.brandtech.com